

## 545

### **Outdoor Lighting**




#### Your product advantages

- **Efficient**: Use
- ✓ Flexible: Different applications thanks to diffusing or clear glass
- ✓ Reliable: Lifetime of the LED driver and LED modules at 85.000h


#### **Application areas**

Roads in residential areas, squares, paths

#### Dimensions (mm)



# Light distribution (Asymmetric wide beam / Symmetric and diffusing)



### **Technical datasheet**



**Street optic Symmetric diffusing** 545

343	Street optic	Symmetric unrusing
Lighting fixtures body		
Material	Aluminium (shade) / Die cast aluminium (dome)	
Colour (powder coating)	RAL or DB	
Mounting type	Post top mounting (Ø 76 mm)	
Orientation possibilities	-	_
Dimension (height x diameter)	555 x Ø 650 mm	
Weight	app. 12 kg	
Exposed wind surface	0.15	m <sup>2</sup>
IP Protection class	IP 65	
Glass type	PMMA (tranparent)	PMMA (opal)
Shock resistance	IK 08	
Photometric properties		
Light source	LED modules with High-Power LEDs	
Optical system	Asymmetric wide beam / Roto- symmetric	Symmetric and diffusing beam
Rated luminous flux	1,100 – 2,600 lm	900 – 3,200 lm
Light efficiency	110 lm/W	90 lm/W
Colour temperature	3.000 / 4.300 K	3.000 / 4.000 K
Colour rendering index (Ra)	> 70	
Dimming (power control)	Power line control / Digital	
Rated lifetime at (ta) 30°C	85,000 h at L70	
Temperature management	✓	
Constant Light Output (CLO)	✓	
Electrical properties		
Rated power	10 – 24 W	10 – 36 W
Electrical protection class	Class I / II	
Rated voltage	120 – 277 V	
Frequence	50 – 60 Hz	
Surge protection (L-N / L N-ground)	6/8 kV	
Installation suggestions		
Application areas	Roads in residential areas	Squares, paths
Light point height	3 –	5 m
Lighting classes	ME/S	S
Admitted ambient temperature (ta)	-25°C - +35°C	
Other properties		
Certificate	CE	
Connection to circuit breaker (B16)	17 pcs.	
Options		
Reduction part to Ø 60 mm	✓	
Additonal part Over tension resistant	10 kV	
DALI Interface (not at power line control)	✓	





